



## Gauges and Digital Flow Meter to match your application

Additional models, sizes, makes, capacities  
and options are available.

*Please contact us for information, consulting or engineering assistance.*

## Digital Flow Meter

	DM 50	DM 30	DM 03
<b>Flow range</b>	3 – 50 GPM (10 – 200 l/min)	3 – 30 GPM (10 – 100 l/min)	0.3 – 3 GPM (1 to 10 l/min)
<b>Typical accuracy</b>	+/- 1.5% (field calibrated)	+/- 5% (factory calibrated)	+/- 1.5% (field calibrated)
<b>Maximum Pressure Drop</b>	2 PSIG (0.14 bar) @ full flow	1.7 PSIG (0.12 bar) @ full flow	2 PSIG (0.14 bar) @ full flow
<b>Port size</b>	1" NPT	1" NPT	1" NPT
<b>Power</b>	Lithium Batteries (included)	2 x AAA batteries (included)	Lithium Batteries (included)
<b>Electronic features</b>	Flow rate, resettable count non-resettable cumulative count	resettable batch count non-resettable cumulative count	Flow rate, resettable count non-resettable cumulative count
<b>Weight</b>	2 lbs (0.9kg)	2 lbs (0.9kg)	2 lbs (0.9 kg)

- Designed for outdoor use from 14 to + 130 deg F (-10 to +54 deg C) on fuel transfer applications diesel, gasoline, kerosene and jet fuel.
- For protection, install your digital flow meters inline after a strainer or filter.

## Gauges



	CI-12	CI-20L	PG-30	30652	VG-30
<b>Type</b>	Pressure Gauge	Pressure Gauge	Pressure Gauge	Compound Gauge	Vacuum Gauge
<b>Range</b>	0 -60 PSI Green 0-12 PSI	0-60 PSI Green 0-20 PSI	0-30 PSI Green 0-22 PSI	30" HG – 15 PSI Red Tell-Tale Finger	0-30" HG Green 0-15" HG
<b>Connection</b>	Center Back 1/8" NPT	Center Back 1/8" NPT	Bottom 1/4" NPT	Bottom 7/16-20 SAE	Bottom 1/4" NPT
<b>Design type</b>	Dry, color coded	Liquid Filled, color coded	Liquid filled, Stainless Steel	Liquid Filled, Stainless Steel	Liquid filled, Stainless Steel
<b>Dial Diameter</b>	2"	2"	2-1/2"	2-1/2"	2-1/2"
<b>Weight</b>	3.5 oz	3.5 oz	6 oz	6 oz	6 oz